

Technical Data - 8CH Digital Out Module (101-210110)

Technical Data - 8 Channel Digital Out Module (101-210110)	
Backplane	
Controllers Modules Power supply module electronics Power supply digital outputs Current consumption module electronics Compatible backplane units	Web server, PROFINET IO device, PROFIBUS DP slave 32 (all slots) Provided through the backplane Provided through an additional 3-pin connector ± 290 mA 101-200011, 101-200023, 101-200012
Digital Outputs	
Outputs Current Voltage range Losses	8 DOs on 1 connector 0.5 A per DO (direct current) 15..30 VDC (depends on provided voltage) 0.211 Ohm loss per DO
Power Connector	
Pins power connector Wire diameter (for the screw terminals) Wire type	1 = -, 2 = +, 3 = SH < 2.5 mm ² Stranded or solid core
Digital Output Connector	
Pins DO connector Wire diameter (for the screw terminals) Wire type	1 = GND, 2..9 = DO0..DO7, 10 = GND < 1.5 mm ² Stranded or solid core
Others	
Head Station firmware Dimensions Operating temperature Weight MTBF	V1.260 and later 140 x 110 x 25 mm 0 .. 60 °C 105 g To be defined
PROCEN TEC Turfschipper 41 2292 JC WATERINGEN (NL)	Tel.: +31-174-671800 Fax: +31-174-671801 Email: info@procentec.com